


DF-5015/DF-5015C


Outdoor DFIR™ detector



Optical View Pattern



M-5015



M-5015C


Product Features

- **Split-View™**DFIR™**** electro-optical systems, the two patents
- **SureTrac™**** curtain in detection range is always the same width, 90° vertical coverage throughout the detection area (For DF-5015C)
- Sealed IP65 construction
- Continuous supervision of: Power supply voltage range; Ambient temperature range; IR detector operational parameters
- Look-down detection directly below the sensor to catch wall-crawling intruders
- Sensitive tamper detection switch
- Tightly-mated bug guard to protect the sensor optics from insects, spiders and dust
- Selectable processing sensitivity for different environmental requirements
- Operation from -40C to +55C
- Multiple white light immunity features

Specifications

Detection Range	15m				
Detection Angle	90				
Power Supply	Voltage		Current		
	8 – 16V DC		14 mA at 12V DC		
Alarm Relay	Solid state Form A (NC) 50 mA 30V; 1500 Vrms iso				
Tamper Switch	Form A (NC) 50 mA @ 30V DC				
RF Immunity	20V/m 10-1000MHZ; 10V/m 1000-2000MHZ				
White-light Immunity	25,000lux				
Environmental	-40C to +55C operation; IP65				
Housing	High-impact ABS				
Dimensions	167 X 76 X 42 (H X W X D)				
Optical fields-of-view	Model	Long Range	Mid Range	Short Range	Look-down
		DF-5015	88	30+8	18+8
	DF-5015C	4	4	8	2

Accessories



MB-200: Rotating wall mount bracket