

**SD-305W**

Wireless Smoke Detector with low-battery alert

**Specifications**

	SD-305W
Monitoring area	20 m <sup>2</sup>
Alarm concentration	m = 0.5 dB / M ( meet GB4715-1993 )
Alarm	Wireless Alarm ( Independent )
Sound level	≥ 85 db / m
Operating Frequency	433.92MHz ± 75KHz
Transmission Distance	100 m ( Open )
Input Voltage	9 V DC
Current	≤ 15 uA ( Standby ) ; ≤ 30 mA ( Alarm )
Battery Life	1 year ( 6F22 battery / 200 mAH )
Tamper Switch	yes
Operating temperature	-10℃ ~ +50℃
Dimensions	R: 107 mm , H: 35 mm
Weight	92 g ( Without batteries )

**GD-205W**

Wireless Gas Detector

**Specifications**

	GD-205W
Alarm concentration	10 ~ 25% ( Natural gas, LPG , coal gas )
Alarm	Wireless Alarm ( Independent )
Sound level	≥ 85 db / m
Operating Frequency	433.92MHz ± 75KHz
Transmission Distance	100 m ( Open )
Input Voltage	100~240V Input, 12V DC
Current	≤ 80 mA ( Standby )
Operating temperature	-10℃ ~ +50℃
Dimensions	116 x 73 x 43 mm
Weight	206 g